

## AMD Product Brief - Preliminary Information

# AMD-8132™ HyperTransport™ PCI-X® 2.0 Tunnel

## Product Overview


The AMD-8132™ HyperTransport™ PCI-X® 2.0 tunnel developed by AMD provides two PCI-X bridges designed to support PCI-X 266 transfer rates<sup>1</sup>. The AMD-8132 tunnel is compliant with *HyperTransport™ I/O Link Specification, Rev 2.0* including errata up to specification Rev 1.05c. The package is a 31 x 31 millimeter, 829 ball, flip-chip organic BGA. The core is 1.2 volts. Power dissipation is 7 watts.

### HyperTransport™ Features:

- HyperTransport tunnel with side 0, 16-bit input/16-bit output; and side 1, 16-bit input/16-bit output.
- Either side can connect to the host or to a downstream HyperTransport technology compliant device.
- Each side supports HyperTransport technology-defined reduced bit widths: 8-bit, 4-bit, and 2-bit.
- Each side supports transfer rates of 2000, 1600, 1200, 1000, 800, and 400 mega-bits per second per wire.
- Maximum bandwidth is 8 gigabytes per second across each side (half upstream and half downstream).
- Independent transfer rate for each side and each direction.
- Independent bit width selection for each side and each direction.
- Link disconnect protocol supported.
- HyperTransport interrupt control support.
- 64-bit address support.

### PCI-X® Features:

- Two PCI-X bridges: bridge A and bridge B.
  - Each bridge supports a 64-bit data bus.
  - Each bridge supports Mode 1 PCI-X and Conventional PCI protocol. Each bridge is designed to support Mode 2 operation.<sup>1</sup>
  - In PCI-X Mode 2, bridges are designed to support transfer rates of 266 and 200 MHz.<sup>1</sup>
  - In PCI-X Mode 1, bridges support transfer rates of 133, 100, 66, and 50 MHz.
  - In PCI mode, bridges support transfer rates of 66, 50, 33, and 25 MHz.
  - Independent transfer rates and operational modes for each bridge.
  - Each bridge includes support for up to 5 PCI masters with clock, request, and grant signals.
  - Each bridge includes a HyperTransport™ technology compliant interrupt controller. Legacy interrupt controller and IOAPIC modes are also supported.
  - Each bridge can receive PCI device interrupts via INTA/B/C/D pins or via MSI/MSI-X transactions.
  - SHPC-compliant hot-plug controller and support.
- PCI-X Mode 2, 1.5 V link signaling. PCI-X Mode 1, 3.3 V link signaling. PCI, 3.3 V link signaling.



**AMD-8132™ HyperTransport™ PCI-X® 2.0 Tunnel**

1. Mode 2 operation is being evaluated.

© 2002, 2003, 2004 Advanced Micro Devices, Inc.

All rights reserved. The contents of this document are provided in connection with Advanced Micro Devices, Inc. ("AMD") products. AMD makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. No license, whether express, implied, arising by estoppel or otherwise, to any intellectual property rights is granted by this publication. Except as set forth in AMD's Standard Terms and Conditions of Sale, AMD assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right. AMD's products are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or in any other application in which the failure of AMD's product could create a situation where personal injury, death, or severe property or environmental damage may occur. AMD reserves the right to discontinue or make changes to its products at any time without notice.

### **Licensed Technology**

PCI-X and PCI Hot Plug technology developed by Compaq/Hewlett Packard Corporation.

### **Trademarks**

AMD, the AMD Arrow logo, and combinations thereof, and AMD-8132 are trademarks of Advanced Micro Devices, Inc.

HyperTransport is a licensed trademark of the HyperTransport Technology Consortium.

PCI-X is a registered trademark of the PCI-SIG Corporation.

Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies.